








An ISO 9001:2008 & 14001:2004 Certified Co.

## PRODUCT OVERVIEW

D.W.A.R is a single component, solvent base chemical with excellent gloss and colour retention. It is tintable in a wide range of colours. It has good water resistant property. Various features such as :

- » Dust, Water, Acid & Rust Proof.
- » Single component coating.
- » Transparent glossy film
- » Can be applied on any surface ( cement, stone, wood, plastic, iron etc.)
- » Can be applied by spray/brush/cotton.
- » Washable film.

PRODUCT BENEFITS	PACKING
<ul style="list-style-type: none"> <li> Water Repellent</li> <li> Dust Repellent</li> <li> Acid Proof</li> <li> Rust Repellent</li> </ul>	<ul style="list-style-type: none"> <li>■ 5 Ltr.</li> <li>■ 1 Ltr.</li> </ul> <div style="text-align: right; margin-top: 20px;">  </div> <p style="font-size: small; margin-top: 10px;">Shelf life : 3years from the date of manufacture in original tight closed containers away from direct sunlight and excessive heat.</p>

## TECHNICAL SPECIFICATION

Properties	Viscosity	Color	Surface Drying Time
» Solvent Base Transparent Coat. » Acid Proof, Dust Repellent » Water Repellent, Rust Repellent	16.46 Sec	Yellow Transparent	5-10 Min @ 25°C
<b>Solid Content By Weight</b>	<b>Complete Curing</b>		<b>Water Absorption (After Cure)</b>
approx 15%	24Hours @ 25°C		Negligible
<b>Water Permeability</b>	<b>Adhesion Strength</b>		<b>Density</b>
Negligible	Excellent		0.90 Gm/cc
<b>Sofetning Point</b>	<b>Storage &amp; Pot Life</b>		<b>Coverage</b>
90°C	36 Months   Store Between 10 To 35°C		35 to 45 Sq ft (Depends on Surface porosity)

Note : The Product material can be renewed by the company for the betterment at anytime without any notice/information.

## SURFACE PREPARATION

- Clean the Surface thoroughly, as it should be free from dust, oil and etc.
- Remove existing Paint Layer/ Coating before applying "D.W.A.R"
- It is recommended to use wire brush followed by sanding with emery.
- Water wash the surface before "D.W.A.R" Application.



## APPLICATION PROCEDURES

- Apply 2-3 coats with spray, sponge or brush uniformly (wait for at least 30 minutes. after each coat.)
- Before application surface should be dry fully.

### Caution

The applicators and operators must be trained, experienced and have the understanding and equipment to mix/stir and apply the coatings correctly and according to Nushar technical protocol. Applicators and operators shall use appropriate personal protection when using these products.

### Health and safety

Please study the safety precautions mentioned on the container. Apply the products under well ventilated conditions. Ensure that spray mist is not inhaled and skin contact with the product should be avoided. Spillage on the skin should immediately be removed with suitable cleanser, soap and water. If the eyes feel any burning sensation then they should be flushed with ample water and the Doctor should be immediately consulted.

**Note: We do not undertake any legal obligation for the product as its proper application is equally important. We accept no legal responsibility for the work done even by trained applicators as we have no control over what they are actually doing on the site. The consumer has to first satisfy himself/herself by observing work done by us & by visiting our display gallery.**

All subject to the jurisdiction of courts in Jodhpur, Rajasthan.